

# ***TECHNICAL BULLETIN***

## ***MOTORSILK CLS BOND®*** **ENGINE TREATMENT**

### DESCRIPTION:

Motorsilk CLS Bond Engine Treatment additive is designed to extend the life and operating range of your engine. It blends with your existing engine oil and contains boron-based components that protect vital working parts from friction and corrosive elements.

Motorsilk CLS Bond Engine Treatment actually forms a near-diamond hard surface on metal parts, providing a super-slick surface. The new surface also blocks oxygen to prevent corrosive activity. This micro-layer of protection is bonded to metal surfaces with strong covalent and ionic bonds. It provides long-lasting, low-friction surface impervious to most contaminants.

### USAGE:

Motorsilk CLS Bond Engine Treatment works with any four-cycle engine when added to the crankcase oil at a 10:1 ratio. A single pint container treats a normal five-quart crankcase.

### APPLICATIONS:

All internal combustion, four-cycle engines of any horsepower can benefit from this one-time treatment.

### SPECIFICATIONS:

Color..... Translucent Tan  
Base Fluid..... Full Synthetic  
Viscosity..... 20 W 50  
Flash point..... 180 C.  
Solids..... Boron Variants  
D.O.T..... Unregulated  
V.O.C. .... None  
Biodegradable..... Yes

### PACKAGING:

16-Oz. (Pint), 5 Gal Pails, 55 Gal Drums